



MASTER SİLİKONLU MATT

DESCRIPTION: Acrylic emulsion adhesive-based , silicone additives, matte outward looking, water based ,first class finish interior wall paint.

CHARACTERISTIC: -Healthy and environmental friendly -Easily applicable and leaves no remainings. - High covering ability. -Matte outward looking, colourfast for years

APPLICATION SURFACES: Master Silikonlu Matt can be applied on a wide range of interior old painted surface s such as concrete , plaster , wall paints , glass textile etc.

TECHNICAL INFORMATION: Consumption: Single coat: 12- 16 (m²/lt) Thinner: Water Thinning Ratio: %10- 15 Drying: Touch dry: after 15-20 min, Dust repulsive: after 1 hour, Hard dry: after 24 hours Viscosity: 125 KU ± 10 (23 ° C) pH: 8 – 9 Density : 1,47 ± 0,02 (gr / cm³)

SURFACE PREPARATION -The Surface should be free from all kind of dust . Loose and old paintings should be scraped and surface should be dry. -Hollows and cracks should be filled with Master Silikonlu Matt, Acrylic Putty in case of necessity. -For the surfaces which were not painted before , it is recommended first to use Silkcoat Izolac. Use Master Universal Primer for old synthetic painted surfaces and Master Putty Primer for primed surfaces. .

APPLICATION: -Master Silikonlu Matt should be thinned 10-15% with clean water and applied with roller , brush or spraying in two coats. -Leave minimum 2 hours between coats depending on weather conditions. -After application , tools should be cleaned with water.

APPLICATION DETAILS: -On new painted surfaces , make sure that surface has waited about 28 days before application. - Master Silikonlu Matt should be completely mixed so that it is homogenous. -Do not apply below 5C. -Gloss and glasslike surface should be rubbed before application to obtain better adhesiveness and a healthy surface .

CAUTION: -Avoid getting eye and skin contact. In case wash with plenty of water. -Preserve in a tightly closed container. -Keep high that children cannot reach. -Do not pour into sewer system.

STORAGE: Keep at a cool and clean place away from sun light. It can be stored unopened 1 year at room temperature. **PACKAGING:** 20 Kg 10 Kg 4 Kg PE Bucket

QUALITY CERTIFICATE: Found complying as per TS 5808 Conditions