



MASTER EKO

DESCRIPTION: Acrylic copolymer adhesive based ,matt outward looking , economical interior paint.

CHARACTERISTIC:

- Breathable and adhesive
- High covering ability

APPLICATION SURFACES:

Can be applied on all kinds of prepared and clean surfaces.

TECHNICAL INFORMATION:

Structure: Acrylic copolymer adhesive

Consumption: Single coat: 7-8 (m²/kg)

Thinning Ratio: % 15-20 with water

Application tools: Brush, Roller

Drying: Touch dry: after 15-20 minutes; Hard Dry: after 2 hours

Viscosity: 125 KU $\pm$ 10 (23 ° C)

pH: 8 - 8,5

Density: 1,66 gr / cm³ $\pm$ 0,02

Amount of solid: (64 $\pm$ 2) %

Brilliance: 85° 'de 7 $\pm$ 3

Thickness of dry coat: (50 $\pm$ 5) micron

Thickness of wet coat: (120 $\pm$ 5) micron

SURFACE PREPARATION:

— All loose paints should be scraped and cracks should be filled with recommended Primer to obtain a smooth surface.

— Master Eco can be applied 8-12 hours later on prepared surfaces after recommended Primer has been applied.

APPLICATION DETAILS:

—Dont apply under + 5°C

CAUTION:

- Avoid getting eye and skin contact. In case wash with plenty of water.
- Preserve in a tightly closed container.
- Keep above the reach of children
- Do not dump into sewer system.

STORAGE: STORAGE

Keep at a cool and clean place away from sun light. It can be stored unopened 1 year at room temperature.

PACKAGING: 20 Kg -10 kg Plastic