



MASTER EXTERIOR PAINT

DESCRIPTION: Silicone based , matt , water based ,first class exterior paint.

CHARACTERISTIC:

- Water resistant , adhesive, modified by silicone exterior topcoat paint.
- No swelling or scraps through its silicone structure.
- Resistant against rain ,snow , and UV.
- High resistant against corrosion on surfaces particularly near sea.

APPLICATION SURFACES:

Can be applied on exterior surfaces such as plaster , concrete finishes and similar surfaces.

TECHNICAL INFORMATION:

Consumption: Single coat: 12- 14 (m²/lt) ; Double coat : 5 - 6 (m²/lt)

Thinner: Water

Thinning Ratio: % 10-15

Density: 1,53 ± 0,02 (g / cm³)

Drying: Touch dry: after 15-20 minutes, Dust repulsive : after 1 hour, Hard dry: after 24 hours

Viscosity: 115 KU ± 10 (23 ° C)

pH: 8 – 8,5

Brilliance: at 85° 7 ± 3

Thickness of dry coat: (40 ± 5) micron

Thickness of wet coat: (90 ± 5) micron

SURFACE PREPARATION:

- The surface should be free from all kind of dust . Loose and old paintings should be scraped and surface should be dry.

-After hollows and cracks should be filled with Master Exterior Acrylic Putty , Master Exterior Primer is applied.

APPLICATION:

-Master Exterior should be thinned % 10- 15 with water , and applied in 2 coats with roller ,brush or spay gun.

-Leave minimum 2 hours between coats depending on weather conditions.

-After application ,tools should be cleaned with water.

APPLICATION DETAILS:

-On new painted surfaces , make sure that surface has waited about 28 days before application.

-Before application Master Exterior should be completely mixed so that it is homogenous.

-Do not apply below 5 C.

-Gloss and glasslike surfaces should be rubbed before application to obtain better adhesive and a healthy Surface .

CAUTION:

-Avoid getting eye and skin contact. In case wash with plenty of water.

-Preserve in a tightly closed container.

-Keep above the reach of children

-Do not dump into sewer system.

STORAGE:

Keep at a cool and clean place away from sun light. It can be stored unopened 1 year at room temperature.

PACKAGING:

20 kg PE Bucket

QUALITY CERTIFICATE:

Found complying as per TS 7847 conditions.