



## **MASTER MARMARITO**

**MARMARITO DESCRIPTION:** Acrylic Copolymer adhesive based ,marble patterned decorative interior wall paint.

**CHARACTERISTIC:** -Harmless to people and environmental friendly through its water based content. Suits your personal pleasure with its marble pattern , and velvety structure. -High covering ability. Leaves no cracks. -Effeceable.

**APPLICATION SURFACES:** Marmarito can be used on all appropriately prepared wood, concrete, concrete panel, conventional plaster etc. surfaces.

### **TECHNICAL INFORMATION**

Consumption: 1,5- 2 m<sup>2</sup>/ kg

Thinner: No thinning , ready to-use

Drying: Touch dry: after 15-20 min,

Dust repulsive: after 1 hour,

Hard dry: after 24 hours

**SURFACE PREPARATION:** -The surface should be free from all kind of dust . Loose and old paintings should be scraped and surface should be dry. -In case that surface is not smooth , to be able to apply Marmarito on the surface first apply Master Interior Acrylic Putty to obtain problem-free surface. -A smooth and glazed surfaces should be obtained by applying Izolac before Marmarito application. Smooth but old painted, sytnthetic and dirty surfaces should be obtained by applying Master Universal Primer . A surface which has been puttied should be obtained by applying Master Putty Primer.

**APPLICATION:** -Master Marmarito can be applied without diluting through spatula in two coats. -Leave minimum 4 hours between coats depending on weather conditions. -After 2. coat application is dry ,marmarito is applied with spatula without diluting again giving diagonal and vertical-horizontal non continous spatula or trowel strikes to make material textured on surface. - As a last step , entire surface

is shined by putting pressure on trowel with up-down and right-left circular movements . Different colors can be obtained one one another. -After application , tools should be cleaned with water.

APPLICATION DETAILS: - Marmarito should be completely mixed so that it is homogenous. - Do not apply under 5 C. - Gloss and glasslike surfaces should be rubbed before application to obtain better adhesive and a healthy surface .

CAUTION: -Avoid getting eye and skin contact. In case wash with plenty of water. -Preserve in a tightly closed container. Keep above the reach of children -Do not dump into sewer system.

STORAGE: Keep at a cool and clean place away from sun light. It can be stored unopened 1 year at room temperature.

PACKAGING: 12kg , 4kg ,1 Kg PE Bucket