



## MASTER OIL PAINT/SYNTHETIC PAINT

OIL PAINT DESCRIPTION : Alkyd resin based , synthetic , glossy paint for topcoat applications.

CHARACTERISTIC : High covering ability. -Doesnt turn to yellow. -Adhesive -Easily appliable. -Resistant against physical and chemical impacts. -Effeceable and flexible. -Glossy outward looking.

APPLICATION SURFACES: Can be applied on kinds of exterior and interior surfaces such as wooden ,plaster ,metal and land , marine vehicles as well.

### TECHNICAL INFORMATION

Structure: Alkid resin

Consumption: 6-7 (m<sup>2</sup>/lt)

Thinning Ratio: Brush or roller % 5-10, spray % 15 - 25 with synthetic thinner.

Recommended Primer: Master Universal Primer, Master Synthetic Primer.

Application tools: Brush , roller , spray.

Drying: Tocuh dry; after 1 - 2 hours;

Dust safe; after 2 - 3 hours

Hard dry; after 10 - 12 hours. It should ne waited 12 hours between layers.

Viscosity : 100 KU  $\pm$  10 ( 23 ° C )

Density : 1,21  $\pm$  0,05( g / cm<sup>3</sup> )

Amount of solid : 71  $\pm$  0,2%

Brilliance : ( 60° Minimum 80 Gloss )

Thickness of dry coat: 25  $\pm$  5 micron

Thickness of wet coat: 60  $\pm$  5 micron

**SURFACE PREPARATION:** - Master Synthetic Primer is applied after putty application. -On wooden surfaces, all knots should be burned and Master Synthetic Primer applied after surface has been filled up with Master Wood Protector -Luxe synthetic is applied after 24 hours from Primer application.

**CAUTION:** -Avoid getting eye and skin contact. In case wash with plenty of water. -Preserve in a tightly closed container. -Keep above the reach of children -Do not dump into sewer system.

**STORAGE:** Keep at a cool and clean place away from sun light. It can be stored unopened 1 year at room temperature.

**PACKAGING:** 0,8 Kg- 3,2 Kg-18 Kg.

**QUALITY CERTIFICATE:** Found complying as per TS 39 conditions