



MASTER SUKES

DESCRIPTION: Elastomeric , modified by resins , excellent water resistant flexible isolation material

CHARACTERISTIC : Developed for water isolation.

Water resistant , flexible ,durable against mechanical impacts.

APPLICATION SURFACES: Can be applied on surfaces such as basement ,wall , terrace and similar .

TECHNICAL INFORMATION:

Structure: Liquid Plastic

Consumption: Vertical Surface; 0,75kg / m².Horizontal Surface ;1,5 kg / m²

Thinning Ratio: For first coat % 30 - 40

Application tools: Roller and brush.

Ph: 8 - 9

Intensity: $1,29 \pm 0,02$ (g / cm³)

Amount of solid: ($66,5 \pm 2$)%

Thickness of dry coat: (900 ± 100) Micron

Thickness of wet coat: ($0,17 \pm 0,2$) cm

SURFACE PREPARATION:

Loose and old paintings should be scraped .

Surface should be free from all kinds of grease , dust ,dirt and rust . surface should be obtained as dry.

APPLICATION DETAILS:

Dont apply under + 5°C .Apply first coat as a primer diluted with water % 30-40.After drying apply second and third coat without dilution.

CAUTION:

- Avoid getting eye and skin contact. In case wash with plenty of water.
- Preserve in a tightly closed container.
- Keep above the reach of children
- Do not dump into sewer system.

STORAGE: STORAGE

Keep at a cool and clean place away from sun light. It can be stored unopened 1 year at room temperature.

PACKAGING:

20 kg - 10 kg – 3 kg